Bipolar Plate-Supported Solid Oxide Fuel Cell

J-M. Bae, J.D. Carter, T.A. Cruse, J.M. Ralph, M. Krumpelt, R. Kumar Chemical Technology Division, Argonne National Laboratory







Objective

SOFC for Auxiliary Power Unit (APU) of Automotive Application

Our new concept addresses shortcomings of current SOFC designs

Advantages of SOFC for APUs

- High Power Density and Efficiency
- Fuel Versatility
- Highly Favorable Duty Cycle

Requirements for SOFC APUs

- Quick Start
- Vibration and Shock Resistance
- Low Cost



In support of SECA(Solid State Energy Conversion Alliance), DOE/FE
Chemical Technology Division

Approach

Argonne's new TuffCell SOFC concept meets the APU requirements

- Metal-supported design
- High mechanical strength
- Easy fabrication and cell stacking
- High performance
- Low cost





The Argonne TuffCell

Cathode (ceramic)


Electrolyte (ceramic)

Anode (cermet)


Anode flow field (metal)


Interconnect (metal)

Cathode flow field (metal)



Microstructure of TuffCell











The TuffCell has High Strength







Preliminary Performance of TuffCell







Current Status of TuffCell

- New fabrication concept greatly reduces fabrication problems
- High mechanical strength has been confirmed
- Theoretical OCV (open circuit voltage) was obtained
- Performance improvements are on-going



Next Steps

- Increase performance to ≥ 0.3 W/cm²
- Scale up fabrication to ~100 cm²
- Conduct cycling tests between 25°C and 800°C
- Investigate different cell stacking concepts
- Verify performance on reformate

